

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

Section 1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name	Emulsione Epossidica 723 C.A
--------------	------------------------------

1.2 Relevant identified uses of the substance or mixture and uses advised against

Intended use

Hardener for protective paint based on epoxy resins emulsified in water.

Uses advised against

Usò al consumo

1.3 Details of the supplier of the safety data sheet

Company name	TORGGLER S.R.L.
Full address	Via Prati Nuovi 9
Town	Marlengo
Postal code	39020
Province	BZ
Country	Italy
Phone number	+39 0473 282400
Fax	+39 0473 282501
e-mail address of the competent person responsible for the Safety Data Sheet	reach@torggler.com

1.4 Emergency telephone number

For urgent inquiries refer to	+39 348 662 70 93 (08.00 - 17.30)
-------------------------------	-----------------------------------

Section 2 Hazards identification

2.1 Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification

Skin irritation, category 2	H315	Causes skin irritation.
Serious eye damage, category 1	H318	Causes serious eye damage.

2.2 Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms



Signal word

Danger

Section 2

Hazard statements

H315	Causes skin irritation.
H318	Causes serious eye damage.

Precautionary statements

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P280	Wear protective gloves / eye protection / face protection.
P264	Wash exposed body parts thoroughly after handling.
P332+P313	If skin irritation occurs: Get medical advice / attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Supplementary hazard statements

EUH208	Contains • 3,6,9,12-tetra-azatetradecamethylenediamine • 2,2'-DIAMINODIETHYLAMINE • Amines, polyethylenepoly-, tetraethylenepentamine fraction. May produce an allergic reaction.
--------	---

Contains

Linseed oil polymer with bisphenol A, bisphenol A diglycidyl ether, diethylenetriamine, formaldehyde, glycidyl Ph ether and pentaethylenhexamine

VOC (Directive 2004/42/EC)

Two-pack reactive performance coatings for specific end use such as floors.

Volatile organic compounds - ready to use	3 g/l
VOC subcategory limit	140 g/l

Contains biocides. Contains C(M)IT/MIT (3:1) CAS No. 55965-84-9 as a storage preservative against microbial deterioration.

2.3 Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.
The product does not contain substances with endocrine disrupting properties in concentration $\geq$ 0.1%.

Section 3 Composition/information on ingredients
3.2 Mixtures
Linseed oil polymer with bisphenol A, bisphenol A diglycidyl ether, diethylenetriamine, formaldehyde, glycidyl Ph ether and pentaethylenhexamine

Concentration	$11.6 \leq x < 18 \%$
CAS number	68915-81-1
Hazard classification	- Skin Irrit. 2; H315 - Eye Dam. 1; H318

3,6,9,12-tetra-azatetradecamethylenediamine

Concentration	$0.186 \leq x < 0.25 \%$
CAS number	4067-16-7
EC number	223-775-9
INDEX number	612-064-00-2
Registration Number	01-219485826-22-xxxx

Section 3

Hazard classification	- Acute Tox. 4; H302 - Acute Tox. 4; H312 - Skin Corr. 1B; H314 - Skin Sens. 1; H317 - Eye Dam. 1; H318 - Aquatic Acute 1; H400 - Aquatic Chronic 1; H410
M Factor (acute)	1
M Factor (chronic)	1

2,2'-DIAMINODIETHYLAMINE

Concentration	$0.139 \leq x < 0.6 \%$
CAS number	111-40-0
EC number	203-865-4
INDEX number	612-058-00-X
Registration Number	01-2119473793-27-xxxx
Hazard classification	- Acute Tox. 4; H302 - Acute Tox. 4; H312 - Skin Corr. 1B; H314 - Skin Sens. 1; H317 - Eye Dam. 1; H318 - Acute Tox. 2; H330 - STOT SE 3; H335
LC50 (Inhalation vapours):	1.8 mg/l (4h)

Amines, polyethylenepoly-, tetraethylenepentamine fraction

Concentration	$0.139 \leq x < 0.6 \%$
CAS number	90640-66-7
EC number	292-587-7
Registration Number	01-2119487290-37-xxxx
Hazard classification	- Acute Tox. 4; H302 - Acute Tox. 4; H312 - Skin Corr. 1B; H314 - Skin Sens. 1; H317 - Eye Dam. 1; H318 - Aquatic Chronic 2; H411

Propylidynetrimethanol

Concentration	$0.033 \leq x < 0.146 \%$
CAS number	77-99-6
EC number	201-074-9
Registration Number	01-2119486799-10-xxxx
Hazard classification	Repr. 2; H361f

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Section 4 First aid measures

4.1 Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing

Section 4

difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuers protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2 Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3 Indication of any immediate medical attention and special treatment needed

Immediately call a poison center/doctor.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

Section 5 Firefighting measures**5.1 Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2 Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3 Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

Section 6 Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2 Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

Section 6

6.3 Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4 Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

Section 7 Handling and storage

7.1 Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2 Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany)

None

Applicable technical instruction according to Royal Decree 656/2017:

Classification	Storage in fixed containers	Storage in mobile containers
- H315 – Skin Irrit. 2 - H318 – Eye Dam. 1	Not applicable	MIE APQ-10 – Storage in mobile containers

Respect the joint storage conditions established in Royal Decree 656/2017.

7.3 Specific end use(s)

Information not available.

Section 8 Exposure controls/personal protection

8.1 Control parameters

Regulatory references

ACGIH	ACGIH 2026
Ireland-OELV	2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019)

3,6,9,12-tetra-azatetradecamethylenediamine

Predicted no-effect concentration - PNEC

Normal value of STP microorganisms	1.64 mg/l
Normal value in fresh water	0.0025 mg/l
Normal value for fresh water sediment	0.22 mg/kg/d
Normal value in marine water	0.0025 mg/l
Normal value for marine water sediment	0.14 mg/kg/d
Normal value for the terrestrial compartment	0.18 mg/kg/d
Normal value for the food chain (secondary poisoning)	0.29 mg/kg
Normal value for water, intermittent release	0.025 mg/l

Section 8

Health - Derived no-effect level - DNEL / DMEL	Local effect	Systemic effect
Consumers, short-term, dermal	1.59 mg/cm ²	13 mg/kg bw/d
Consumers, short-term, inhalation	Not available	2,542 mg/m ³
Consumers, short-term, oral	Not available	32 mg/kg bw/d
Consumers, long-term, dermal	0.68 mg/cm ²	0.4 mg/kg bw/d
Consumers, long-term, oral	Not available	0.65 mg/kg bw/d
Workers, short-term, inhalation	Not available	8,550 mg/m ³
Workers, long-term, dermal	0.044 mg/cm ²	0.91 mg/kg bw/d
Workers, long-term, inhalation	Not available	1.59 mg/m ³

2,2'-DIAMINODIETHYLAMINE

	TWA		STEL		CEILING		Remarks
	mg/m ³	ppm	mg/m ³	ppm	mg/m ³	ppm	
ACGIH	4.2	1					Skin
Ireland-OELV	4	1					Skin

Predicted no-effect concentration - PNEC

Normal value of STP microorganisms	6 mg/l
Normal value in fresh water	0.56 mg/l
Normal value for fresh water sediment	1,072 mg/kg/d
Normal value in marine water	0.056 mg/l
Normal value for marine water sediment	107.2 mg/kg/d
Normal value for the terrestrial compartment	214 mg/kg
Normal value for water, intermittent release	0.32 mg/l

Health - Derived no-effect level - DNEL / DMEL	Local effect	Systemic effect
Consumers, short-term, dermal	Not available	4.88 mg/kg bw/d
Consumers, short-term, inhalation	Not available	27.5 mg/m ³
Consumers, long-term, dermal	Not available	4.88 mg/kg bw/d
Consumers, long-term, inhalation	Not available	4.6 mg/m ³
Workers, short-term, inhalation		92.1 mg/m ³
Workers, long-term, dermal	1.1 mg/cm ²	11.4 mg/kg bw/d

Amines, polyethylenepoly-, tetraethylenepentamine fraction
Predicted no-effect concentration - PNEC

Normal value of STP microorganisms	4.6 mg/l
Normal value in fresh water	0.0068 mg/l
Normal value for fresh water sediment	0.341 mg/kg/d
Normal value in marine water	0.0068 mg/l
Normal value for marine water sediment	0.746 mg/kg/d
Normal value for the terrestrial compartment	0.274 mg/kg/d

Health - Derived no-effect level - DNEL / DMEL	Local effect	Systemic effect
Consumers, short-term, dermal	1.29 mg/cm ²	10 mg/kg bw/d
Consumers, short-term, inhalation		2,071 mg/m ³
Consumers, short-term, oral		26 mg/kg bw/d
Consumers, long-term, dermal	0.56 mg/cm ²	0.32 mg/kg bw/d
Consumers, long-term, inhalation		0.38 mg/m ³
Consumers, long-term, oral		0.53 mg/kg bw/d
Workers, short-term, inhalation		6,940 mg/m ³
Workers, long-term, dermal	0.036 mg/cm ²	0.74 mg/kg bw/d
Workers, long-term, inhalation		1.29 mg/m ³

Section 8

Propylidynetrimethanol

Health - Derived no-effect level - DNEL / DMEL	Local effect	Systemic effect
Consumers, long-term, dermal		
Consumers, long-term, inhalation	3.3 mg/m ³	580 µg/m ³
Consumers, long-term, oral		

8.2 Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

When choosing risk management measures and operating conditions, consult the exposure scenarios attached.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344/EN ISO 13034).

Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Section 9 Physical and chemical properties
9.1 Information on basic physical and chemical properties

Physical state	viscous liquid	
Colour	various	
Odour	characteristic	
Odour threshold	Not applicable	
Melting point / freezing point	Not available	
Initial boiling point	100 °C (212 °F)	
Flammability	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Flash point	> 60 °C (> 140 °F)	
Auto-ignition temperature	Not available	
Decomposition temperature	Not available	
pH	9.8	Temperature: 23 °C (73.4 °F)

Section 9

Kinematic viscosity	> 20.5 mm ² /s	
Dynamic viscosity	4,400 Pl	Temperature: 23 °C (73.4 °F)
Solubility	miscible	
Partition coefficient: n-octanol/water	Not available	
Vapour pressure	Not available	
Density and/or relative density	1.1 g/ml	Temperature: 20 °C (68 °F) Method: ISO 1675-75
Relative vapour density	Not available	

Particle characteristics

Information not available.

9.2 Other information
9.2.1 Information with regard to physical hazards

Information not available.

9.2.2 Other safety characteristics

Total solids	38.43 %	Temperature: 250 °C (482 °F)
VOC (Directive 2004/42/EC)	0.23 % – 3 g/l	

Section 10 Stability and reactivity
10.1 Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2 Chemical stability

The product is stable in normal conditions of use and storage.

10.3 Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4 Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5 Incompatible materials

Information not available.

10.6 Hazardous decomposition products

Information not available.

Section 11 Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Section 11

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
11.1.1 Metabolism, toxicokinetics, mechanism of action and other information

Information not available.

11.1.2 Information on likely routes of exposure

Information not available.

11.1.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available.

11.1.4 Interactive effects

Information not available.

11.1.5 ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture	> 20 mg/l
ATE (Oral) of the mixture	Not classified (no significant component)
ATE (Dermal) of the mixture	Not classified (no significant component)

3,6,9,12-tetra-azatetradecamethylenediamine

LD50 (Oral):	1,600 mg/kg	Species/guidelines: Rat
ATE (Dermal)	1,100 mg/kg	estimate from table 3.1.2 of Annex I of the CLP

2,2'-DIAMINODIETHYLAMINE

LD50 (Oral):	1,620 mg/kg	Species/guidelines: Rat
LD50 (Dermal):	1,045 mg/kg	Species/guidelines: Rabbit
LC50 (Inhalation vapours):	1.8 mg/l	Exposure duration: 4 hours Species/guidelines: Rat

Linseed oil polymer with bisphenol A, bisphenol A diglycidyl ether, diethylenetriamine, formaldehyde, glycidyl Ph ether and pentaethylenehexamine

LD50 (Oral):	2,960 mg/kg	Species/guidelines: Rat
LD50 (Dermal):	> 5,000 mg/kg	Species/guidelines: Rabbit

Amines, polyethylenepoly-, tetraethylenepentamine fraction

LD50 (Oral):	1,716.2 mg/kg	Species/guidelines: Rat - OCSE 401
LD50 (Dermal):	1,260 mg/kg	Species/guidelines: Rabbit - OECD 404

Propylidynetrimethanol

LD50 (Oral):	14,000 mg/kg	Species/guidelines: Rat
LC50 (Inhalation mists/powders):	> 0.29 mg/l	Exposure duration: 4 hours Species/guidelines: Rat

11.1.6 SKIN CORROSION/IRRITATION

Causes skin irritation.

11.1.7 SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage.

11.1.8 RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

Section 11

11.1.9 GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

11.1.10 CARCINOGENICITY

Does not meet the classification criteria for this hazard class

11.1.11 REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

11.1.12 STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

11.1.13 STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

11.1.14 ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

Viscosity:

11.2 Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

Section 12 Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1 Toxicity**3,6,9,12-tetra-azatetradecamethylenediamine**

EC50 - for Crustacea	18 mg/l	Exposure duration: 48 hours Species/guidelines: Daphnia magna
LC50 - for Fish	133 mg/l	Exposure duration: 96 hours Species/guidelines: Pimephles promelas
EC50 - for Algae / Aquatic Plants	0.7 mg/l	Exposure duration: 72 hours Species/guidelines: Pseudokirchneriella subcapitata

2,2'-DIAMINODIETHYLAMINE

EC50 - for Crustacea	32 mg/l	Exposure duration: 48 hours Species/guidelines: Daphnia magna
LC50 - for Fish	430 mg/l	Exposure duration: 96 hours Species/guidelines: Poecilia reticulata
EC50 - for Algae / Aquatic Plants	1,164 mg/l	Exposure duration: 72 hours Species/guidelines: Pseudokirchneriella subcapitata
Chronic NOEC for Fish	> 10 mg/l	Species/guidelines: Fish (28 d)
Chronic NOEC for Crustacea	5.6 mg/l	Species/guidelines: Daphnia magna (21 d)

Amines, polyethylenepoly-, tetraethylenepentamine fraction

EC50 - for Crustacea	24 mg/l	Exposure duration: 48 hours Species/guidelines: Daphnia magna
LC50 - for Fish	420 mg/l	Exposure duration: 96 hours Species/guidelines: Poecilia reticulata

Section 12

EC50 - for Algae / Aquatic Plants	6.8 mg/l	Exposure duration: 72 hours Species/guidelines: Selenastrum capricornutum - OECD 201
Chronic NOEC for Crustacea	18 mg/l	Species/guidelines: Daphnia magna
Chronic NOEC for Algae / Aquatic Plants	500 mg/l	Species/guidelines: Pseudokirchneriella subcapitata

Propylidynetrimethanol

EC50 - for Crustacea	16,360 mg/l	Exposure duration: 48 hours Species/guidelines: Daphnia magna
----------------------	-------------	--

12.2 Persistence and degradability**3,6,9,12-tetra-azatetradecamethylenediamine**

Degradability	NOT rapidly degradable
---------------	------------------------

2,2'-DIAMINODIETHYLAMINE

Solubility in water	$1,000 \leq x \leq 10,000$ mg/l
Degradability	NOT rapidly degradable

Amines, polyethylenepoly-, tetraethylenepentamine fraction

Solubility in water	1,000,000 mg/l
Degradability	Unavailable

Propylidynetrimethanol

Degradability	Rapidly degradable
---------------	--------------------

12.3 Bioaccumulative potential**2,2'-DIAMINODIETHYLAMINE**

Partition coefficient n-octanol/water	-5.58 LogKow
---------------------------------------	--------------

Amines, polyethylenepoly-, tetraethylenepentamine fraction

Partition coefficient n-octanol/water	-316 LogKow
---------------------------------------	-------------

Propylidynetrimethanol

Partition coefficient n-octanol/water	-2.37 LogKow
---------------------------------------	--------------

12.4 Mobility in soil**2,2'-DIAMINODIETHYLAMINE**

Partition coefficient soil/water	0.531 LogKoc
----------------------------------	--------------

12.5 Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6 Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7 Other adverse effects

Information not available.

Section 13 Disposal considerations

EWC: 080416.

Section 13

13.1 Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Hazardous waste classification - Reg. (UE) 1357/2014

HP 4 – Irritant — skin irritation and eye damage

Section 14 Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1 UN number or ID number

Not applicable

14.2 UN proper shipping name

Not applicable

14.3 Transport hazard class(es)

Not applicable

14.4 Packing group

Not applicable

14.5 Environmental hazards

Not applicable

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable

Section 15 Regulatory information
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU:

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

	Restrictions	Registration Number EU
Product restrictions	3	
Contained substance		
	75	

Section 15

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Not applicable

Substances in Candidate List (Art. 59 REACH)**Registration Number EU**On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.**Substances subject to authorisation (Annex XIV REACH)****Authorisation
Number****Sunset date****Registration Number EU**

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Regulation (EU) 2019/1021 - on persistent organic pollutants

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC)

Two-pack reactive performance coatings for specific end use such as floors.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK2 – Hazard to waters

Regulation (EU) No 528/2012 Biocides

This product contains: C(M)IT/MIT (3:1) CAS No. 55965-84-9 as a storage preservative against microbial spoilage.

15.2 Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

Section 16 Other information**Text of hazard (H) indications mentioned in section 2-3 of the sheet:**

Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 4	Acute toxicity, category 4
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Eye Dam. 1	Serious eye damage, category 1
Repr. 2	Reproductive toxicity, category 2
Skin Corr. 1B	Skin corrosion, category 1B
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H302	Harmful if swallowed.

Section 16

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Legend

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EC50: Effective concentration (required to induce a 50% effect)
- EC: Identifier in ESIS (European archive of existing substances)
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

General Bibliography

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I ATP CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II ATP CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III ATP CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV ATP CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V ATP CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI ATP CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII ATP CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII ATP CLP) of the European Parliament

Section 16

General Bibliography

12. Regulation (EU) 2016/1179 (IX ATP CLP)
13. Regulation (EU) 2017/776 (X ATP CLP)
14. Regulation (EU) 2018/669 (XI ATP CLP)
15. Regulation (EU) 2019/521 (XII ATP CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII ATP CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (EU) 2020/217 (XIV ATP CLP)
19. Delegated Regulation (EU) 2020/1182 (XV ATP CLP)
20. Delegated Regulation (EU) 2021/643 (XVI ATP CLP)
21. Delegated Regulation (EU) 2021/849 (XVII ATP CLP)
22. Delegated Regulation (EU) 2022/692 (XVIII ATP CLP)
23. Delegated Regulation (EU) 2023/707
24. Delegated Regulation (EU) 2023/1434 (XIX ATP CLP)
25. Delegated Regulation (EU) 2023/1435 (XX ATP CLP)
26. Delegated Regulation (EU) 2024/197 (XXI ATP CLP)
27. Delegated Regulation (EU) 2024/2564 (XXII ATP CLP)
28. Regulation (EU) 2024/2865
29. Delegated Regulation (EU) 2025/1222 (XXIII ATP CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Calculation methods for classification

Chemical and physical hazards:
Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards:
Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards:
Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes from the previous revision

This SDS has been prepared with a different software from the one previous revision. The new calculation does not allow us to identify all the differences compared to the previous version. We therefore recommend carefully reviewing all 16 sections of the SDS. We remain available to provide any clarification regarding the content or the changes made compared to the previous version, which is available to professional or industrial users.