

DECLARATION OF PERFORMANCE N. 0046/14

According to Annex III of EU Regulation 305/2011

Unique identification code of the product-type: 0046/14 – Silicone Fire Resistant Grey

Manufacture: Torggler S.r.l., Via Prati Nuovi 9 – 39020 Marlengo (BZ) ITALIA

Harmonised standard and Intended use/es:

EN 15651-1:2012: Sealant for façade for exterior and interior application also used in joints in cold climate areas (F-EXT/INT-CC-25 LM)

Notified Body/ies: 0432 – MPA Materialprüfungsamt Nordrhein-Westfalen (MPA NRW)
1488 – ITB Instytut Techniki Budowlanej (only for fire reaction)


Declared performance: Sample preparation: ISO 8340/A; Substrate: Al_p (Primer Silicone)

The following declared performance applies to all product types specified above.

Essential characteristics		Performance	AVCP-System	Harmonised standard
Reaction to fire		B – s2, d0	3	EN 15651-1:2012
Release of chemicals dangerous to the environment and health		NPD	3	
Durability		Pass criteria	3	
Water tightness and air tightness	Resistance to flow	≤ 3 mm	3	
	Loss of volume	≤ 10%	3	
	Tensile properties at maintained extension after water immersion	NF	3	
	Tensile properties at maintained extension at -30±2°C for cold climates areas	NF	3	
Tensile properties (secant modulus) at -30±2°C for cold climates areas		≤ 0,9 MPa	3	

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance was made in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by



Patrick Ladurner
R&D Sealants & Foams TORGGLER SRL

In accordance with Article 6(5) of Regulation EU 305/2011, a safety data sheet in accordance with Annex II of Regulation EU 1907/2006 (REACH) is provided together with this declaration of performance.