

DECLARATION OF PERFORMANCE N. 0146/20

According to Annex III of EU Regulation 305/2011



Unique identification code of the product-type: 0146/20 – Hybrid LM Bianco
0146/20 – Hybrid LM Grigio
0146/20 – Hybrid LM Nero
0146/20 – Hybrid LM Noce

Manufacture: Torggler S.r.l., Via Prati Nuovi 9 – 39020 Marlengo (BZ) ITALIA

Harmonised standard and Intended use/es:

EN 15651-1:2012: Sealant for façade for exterior and interior application also used in joints in cold climate areas (F-EXT/INT-CC-25LM)

Notified Body/ies: 1292 – Fundacion Tecnalía Research & Innovation

Declared performance: Sample preparation: ISO 8340/B; Substrate: M2_{up}, Al_{up}:

The following declared performance applies to all product types specified above.

Essential characteristics		Performance	AVCP-System	Harmonised standard
Reaction to fire		E	3	EN 15651-1:2012
Release of chemicals dangerous to the environment and health		NPD	3	
Durability		Pass criteria	3	
Water tightness and air tightness	Resistance to flow	≤ 3 mm	3	
	Loss of volume	≤ 10%	3	
	Tensile properties (i.e. elongation): at maintained extension after water immersion	NF	3	
	Tensile properties (i.e. at maintained extension): at -30 °C for cold climates areas	NF	3	
Tensile properties (i.e. secant modulus): at -30 °C for cold climates areas		≤ 0,9 MPa	3	

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance was made in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Patrick Ladurner
Compliance Manager TORGGLER SRL

In accordance with Article 6(5) of Regulation EU 305/2011, a safety data sheet in accordance with Annex II of Regulation EU 1907/2006 (REACH) is provided together with this declaration of performance.