

Unique identification code of the product-type:

0204/22 – Domus Bianco 9010

0204/22 – Domus Bianco 9016

0204/22 – Domus Grigio Chiaro 7047

0204/22 – Domus Avorio 1013

0204/22 – Domus Nero 9005

0204/22 – Domus Antracite 7016

0204/22 – Domus Grigio Sabbia 9002

0204/22 – Domus Testa di Moro 8022

Manufacture: Torggler S.r.l., Via Prati Nuovi 9 – 39020 Marlengo (BZ) ITALIA

Harmonised standard and Intended use/es:

EN 15651-1:2012: Sealant for façade for exterior and interior application also used in joints in cold climate areas (F-EXT/INT-CC-25 LM)

EN 15651-2:2012: Sealant for glazing also used in joints in cold climate areas (G-CC 25 LM)

EN 15651-3:2012: Sealants for sanitary joints (S1)

EN 15651-4:2012: Sealant for movement joints in floors for exterior and interior use also used in joints in cold climate areas (PW-EXT/INT-CC)

Notified Body/ies: 1292 – Fundacion Tecnalía Research & Development

Declared performance: Sample preparation: ISO 8339/A; Substrate: G_{up}, Al_{up}: EN 15651-1:2012
Sample preparation: ISO 8339/A; Substrate: G_{up}: EN 15651-2:2012
Sample preparation: ISO 8339/A; Substrate: G_{up}: EN 15651-3:2012

The following declared performance applies to all product types specified above.

Essential characteristics		Performance	AVCP-System	Harmonized standard
Reaction to fire		E	3	EN 15651-1:2012 EN 15651-2:2012 EN 15651-3:2012
Release of chemicals dangerous to the environment and health		NPD	3	
Durability		Pass criteria	3	
Water tightness and air tightness	Resistance to flow	≤ 3 mm	3	
	Loss of volume	≤ 10%	3	EN 15651-1:2012
	Tensile properties (i.e., elongation): at maintained extension after water immersion at 23 °C	NF	3	
	Tensile properties (i.e. elongation): after immersion in water at 23°C	≥25%		EN 15651-3:2012
	Tensile properties (i.e., at maintained extension at -30 °C)	NF	3	EN 15651-1:2012 EN 15651-2:2012
	Tensile properties (i.e., secant modulus at -30 °C)	≤ 0,9 MPa	3	
	Adhesion/cohesion properties after exposure to heat, water and artificial light	NF	3	EN 15651-2:2012
	Elastic recovery	≥70% at 100 % elongation	3	EN 15651-2:2012
	Tear resistance	NF		
	Adhesion/ cohesion properties at maintained extension after 28 days salt water immersion	NF		
Microbiological growth		1	3	EN 15651-3:2012

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance was made in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by



Patrick Ladurner
R&D Sealants & Foams TORGGLER SRL

As In accordance with Article 6(5) of Regulation EU 305/2011, a safety data sheet in accordance with Annex II of Regulation EU 1907/2006 (REACH) is provided together with this declaration of performance.